

MotorGuard Order Form Guidelines

Date:

Submitted By

End User

Sales Office:	Customer:
Contact:	Contact:
Address:	Address:
City: State: Zip:	City: State: Zip:
Email:	Email:
Tel: () Fax: ()	Tel: () Fax: ()

MotorGuard (please circle correct choice)

Operating Voltage Type: AC DC	Operating Voltage Level:
Motor Control: __ VFD HorsePower____ __ Solid State Starter __ Full Voltage Starter	120/240 480 600 900 2300 4160 6900 7200 13.8KV Other:_____
MotorGuard Type: Single Motor Multiple Motor (600V or less ONLY)	
If a Multiple Motor What Quantity: 4 6 8 9 Other:	
Input Voltage Available: 24 VDC (500/1000V model only) 120VAC 240VAC 50Hz 60Hz	

Installation

If Wall Mount Enclosure What Type:	Suggested Size:_____
NEMA 12 Steel NEMA 4X Stainless Steel NEMA 4X Fiberglass Other:_____	
Type of Alarm Required: Single Alarm Pre-Alarm/Alarm	
Type of Meter Indication Required: __ 1% Analog Switchboard __ 2% Analog Panel Meter	

Digital Meters

Bargraph ____ Digital Meter____ (PICK AN OPTION)
Protocol: USB ASCII__ RS232 ASCII __ USB, Modbus__ RS-485 ASCII__ RS-232 Modbus RTU__ RS-485 Modbus RTU__ Ethernet ASCII__ Ethernet Modbus TCP__

Remote Monitoring Option

4-20mA Transducer_____
